

## 270-1010 被覆PVC金屬軟管 PVC Jacketed Galvanized Steel Flexible Conduits (Liquidtight)



編號 Cat. No.	規格 Sizes	內徑 I. D.		外徑 O. D.		包裝 Std. Pkg. M
		最小 mm	最大 mm	最小 mm	最大 mm	
黑色 (Black)						
S - J02 B	1/4 "	7.9	8.4	11.3	11.8	100
S - J02.5B	5/16 "	10.3	10.8	14	14.5	50
S - J03 B	3/8 "	12.3	12.8	16	16.5	50
S - J04 B	1/2 "	15.8	16.3	20	20.5	50
S - J06 B	3/4 "	20.6	21.1	24.8	25.3	50
S - J08 B	1 "	25.9	26.4	30.7	31.2	50
S - J10 B	1 1/4 "	34.6	35.1	40.5	41	30
S - J12 B	1 1/2 "	40.2	40.7	46.1	46.6	25
S - J16 B	2 "	50.4	50.9	58.6	59.1	20
S - J20 B	2 1/2 "	63.3	63.8	72.9	73.4	10
S - J24 B	3 "	77.8	78.3	86	86.7	10
S - J32 B	4 "	100.3	100.8	111.8	112.5	10

- 產品材質：採鍍鋅鋼板卷繞，外加 PVC 被覆。
- 顏色種類：黑色。
- 產品用途：可繞性 PVC 被覆管，保護電線及絕緣、防水用。
- 使用方式：先將電線穿入管內，再配合金屬軟管固定頭使用即可。  
(請參考本目錄第 280-1010 類 ~ 280-4020 類)



## 270-1020 裸金屬軟管 None Jacketed Galvanized Steel Flexible Conduits (Flame-Retardant)



編號 Cat. No.	規格 Sizes	內徑 I. D.		外徑 O. D.		包裝 Std. Pkg. M
		最小 mm	最大 mm	最小 mm	最大 mm	
S - N02	1/4 "	7.9	8.4	10.9	11.4	100
S - N02.5	5/16 "	10.3	10.8	13.2	13.7	50
S - N03	3/8 "	12.3	12.8	15.1	15.6	50
S - N04	1/2 "	15.8	16.3	19	19.5	50
S - N06	3/4 "	20.6	21.1	24.4	24.9	50
S - N08	1 "	25.9	26.4	29.1	29.6	50
S - N10	1 1/4 "	34.6	35.1	39.4	39.9	30
S - N12	1 1/2 "	40.2	40.7	45.3	45.8	25
S - N16	2 "	50.4	50.9	57.2	57.7	20
S - N20	2 1/2 "	63.3	63.8	70.2	70.7	10
S - N24	3 "	77.8	78.3	80.8	81.3	10
S - N32	4 "	100.3	100.8	108.4	108.9	10

- 產品材質：採鍍鋅鋼板卷繞。
- 產品用途：可繞性無被覆管，保護電線、室內防火用。
- 使用方式：先將電線穿入管內，再配合金屬軟管固定頭使用即可。  
(請參考本目錄第 280-1010 類 ~ 280-4020 類)

