

150-1020

CB-HFT Heat Shrinkable Tubings



Cat. No.	I. D.	Thickness Before Shrinkage	Shrinking Range	Std. Pkg.
	φ mm	mm	φ mm	M
CB - HFT - 1	1.5±0.2	0.18±0.05	1 ~ 0.6	200
CB - HFT - 1.5	2.0±0.2	0.20±0.08	1.5 ~ 0.8	200
CB - HFT - 2	2.5±0.2	0.20±0.08	2 ~ 1	200
CB - HFT - 2.5	3.0±0.2	0.22±0.08	2.5 ~ 1.25	200
CB - HFT - 3	3.5±0.3	0.25±0.10	3 ~ 1.5	200
CB - HFT - 3.5	4.0±0.3	0.25±0.10	3.5 ~ 1.75	200
CB - HFT - 4	4.5±0.3	0.25±0.10	4 ~ 2	200
CB - HFT - 4.5	5.0±0.3	0.25±0.10	4.5 ~ 2.25	100
CB - HFT - 5	5.5±0.4	0.25±0.10	5 ~ 2.5	100
CB - HFT - 6	6.5±0.4	0.28±0.12	6 ~ 3	100
CB - HFT - 7	7.5±0.4	0.30±0.12	7 ~ 3.5	100
CB - HFT - 8	8.5±0.5	0.30±0.12	8 ~ 4	100
CB - HFT - 9	9.5±0.5	0.30±0.12	9 ~ 4.5	100
CB - HFT - 10	10.5±0.5	0.30±0.12	10 ~ 5	100
CB - HFT - 11	11.5±0.5	0.30±0.12	11 ~ 5.5	100
CB - HFT - 12	12.5±0.5	0.30±0.12	12 ~ 6	100
CB - HFT - 13	13.5±0.5	0.36±0.12	13 ~ 6.5	100
CB - HFT - 14	14.5±0.5	0.36±0.12	14 ~ 7	100
CB - HFT - 15	15.5±0.5	0.36±0.12	15 ~ 7.5	100
CB - HFT - 16	16.5±0.5	0.36±0.12	16 ~ 8	100
CB - HFT - 17	17.5±0.5	0.36±0.12	17 ~ 8.5	100
CB - HFT - 18	18.7±0.6	0.40±0.15	18 ~ 9	100
CB - HFT - 20	20.7±0.6	0.40±0.15	20 ~ 10	100
CB - HFT - 22	22.7±0.6	0.40±0.15	22 ~ 11	100
CB - HFT - 25	25.7±0.7	0.40±0.15	25 ~ 12.5	50
CB - HFT - 28	29±0.7	0.45±0.20	28 ~ 14	50
CB - HFT - 30	31±0.7	0.45±0.20	30 ~ 15	50
CB - HFT - 35	36±1.0	0.50±0.22	35 ~ 17.5	25
CB - HFT - 40	41±1.0	0.55±0.25	40 ~ 20	25
CB - HFT - 45	46±1.0	0.55±0.25	45 ~ 22.5	25
CB - HFT - 50	51.5±1.5	0.60±0.25	50 ~ 25	25
CB - HFT - 60	≥ 60	0.60±0.25	60 ~ 30	20
CB - HFT - 70	≥ 70	0.70±0.30	70 ~ 35	20
CB - HFT - 80	≥ 80	0.70±0.30	80 ~ 40	20
CB - HFT - 90	≥ 90	0.70±0.30	90 ~ 45	20
CB - HFT - 100	≥ 100	0.70±0.30	100 ~ 50	20
CB - HFT - 120	≥ 120	0.70±0.30	120 ~ 60	20
CB - HFT - 3 - 1	1.5±0.3	0.10±0.05	1 ~ 0.6	200
CB - HFT - 3 - 1.5	2.0±0.3	0.10±0.05	1.5 ~ 0.8	200
CB - HFT - 3 - 2	2.5±0.3	0.13±0.06	2 ~ 1	200
CB - HFT - 3 - 2.5	3.0±0.3	0.15±0.06	2.5 ~ 1.25	200
CB - HFT - 3 - 3	3.5±0.3	0.15±0.06	3 ~ 1.5	200
CB - HFT - 3 - 3.5	4.0±0.3	0.15±0.06	3.5 ~ 1.75	200
CB - HFT - 3 - 4	4.5±0.3	0.15±0.06	4 ~ 2	200
CB - HFT - 3 - 4.5	5.0±0.3	0.15±0.06	4.5 ~ 2.25	100
CB - HFT - 3 - 5	5.5±0.3	0.15±0.06	5 ~ 2.5	100
CB - HFT - 3 - 6	6.5±0.4	0.15±0.06	6 ~ 3	100
CB - HFT - 3 - 7	7.6±0.4	0.18±0.08	7 ~ 3.5	100
CB - HFT - 3 - 8	8.6±0.4	0.18±0.08	8 ~ 4	100
CB - HFT - 3 - 9	9.6±0.4	0.18±0.08	9 ~ 4.5	100
CB - HFT - 3 - 10	10.6±0.4	0.18±0.08	10 ~ 5	100

CB-HFT

- Material : UL Approved, Halogen-free Polyolefin, low smoke and flame retardant.
- Temperature : 125 °C (257 °F).
- Voltage : CB-HFT (600 V) ; CB-HFT-3 (300 V).
- Application : The CB-HFT series is abrasion resistant and in case of burning, no dioxin is produced which can be used in any enclosed area where a flame-retardant, halogen-free environment is required, such as Metro, Skyscraper, Mass Transit Vehicles and Ships, Electronics component (such as insulation of Capacitors and Resistors), Underground systems, Military and other Industrials.
- **CB-HFT-120** Not yet UL applied, if necessary, the time of purchase, please call the business service queries.