

270-1010

PVC Jacketed Galvanized Steel Flexible Conduits (Liquid-tight)



Cat. No.	Sizes	I. D.		O. D.		Std. Pkg. M
		Min. mm	Max. mm	Min. mm	Max. mm	
S - J02 B	1/4 "	7.9	8.4	11.3	11.8	100
S - J02.5B	5/16 "	10.3	10.8	14	14.5	50
S - J03 B	3/8 "	12.3	12.8	16	16.5	50
S - J04 B	1/2 "	15.8	16.3	20	20.5	50
S - J06 B	3/4 "	20.6	21.1	24.8	25.3	50
S - J08 B	1 "	25.9	26.4	30.7	31.2	50
S - J10 B	1 1/4 "	34.6	35.1	40.5	41	30
S - J12 B	1 1/2 "	40.2	40.7	46.1	46.6	25
S - J16 B	2 "	50.4	50.9	58.6	59.1	20
S - J20 B	2 1/2 "	63.3	63.8	72.9	73.4	10
S - J24 B	3 "	77.8	78.3	86	86.7	10
S - J32 B	4 "	100.3	100.8	111.8	112.5	10

- Material Data : Hot-dipped Galvanized Steel with PVC Jacketed.
- Application : The flexible conduit is manufactured with a spiral wound strip of corrosion / rust resistant, hot-dipped galvanized steel with PVC jacket, which provides liquid-tight and durable crush-proof construction for wire protection.



270-1020

None Jacketed Galvanized Steel Flexible Conduits (Flame-Proof)



Cat. No.	Sizes	I. D.		O. D.		Std. Pkg. M
		Min. mm	Max. mm	Min. mm	Max. mm	
S - N02	1/4 "	7.9	8.4	10.9	11.4	100
S - N02.5	5/16 "	10.3	10.8	13.2	13.7	50
S - N03	3/8 "	12.3	12.8	15.1	15.6	50
S - N04	1/2 "	15.8	16.3	19	19.5	50
S - N06	3/4 "	20.6	21.1	24.4	24.9	50
S - N08	1 "	25.9	26.4	29.1	29.6	50
S - N10	1 1/4 "	34.6	35.1	39.4	39.9	30
S - N12	1 1/2 "	40.2	40.7	45.3	45.8	25
S - N16	2 "	50.4	50.9	57.2	57.7	20
S - N20	2 1/2 "	63.3	63.8	70.2	70.7	10
S - N24	3 "	77.8	78.3	80.8	81.3	10
S - N32	4 "	100.3	100.8	108.4	108.9	10

- Material Data : Hot-dipped Galvanized Steel.
- Application : The flexible conduit is manufactured with a spiral wound strip of corrosion / rust resistant, hot-dipped galvanized steel without PVC jacket, which provides flame-proof, durable crush-proof construction and able to withstand high temperatures for wire protection.

