

270-8010

Nylon Ferrules For Convolved Conduits


PATENTED

RoHS Compliant



Sizes	Cat. No.			For Sizes	Dimensions				Std. Pkg. pcs
	Black RAL 9005	Light Grey RAL 7035	Silver Grey RAL 7001		A mm	B1 mm	B2 mm	C mm	
S - FG02.5	B	G	SG	5/16 "	9.2	20	20.5	20	50
S - FG03	B	G	SG	3/8 "	10.8	20	20.5	21	50
S - FG04	B	G	SG	1/2 "	14.3	25.4	27.5	22	50
S - FG06	B	G	SG	3/4 "	18	30.5	33	24	50
S - FG08	B	G	SG	1 "	23.7	36.5	39.5	28	10
S - FG10	B	G	SG	1 1/4 "	32	45	48	33	10
S - FG12	B	G	SG	1 1/2 "	36	51.6	54.5	36	10
S - FG16	B	G	SG	2 "	49	64.5	67.5	35	10
S - FG24	B	G	SG	3 "	73	94	98.7	48	2

- Material Data : Halogen-free Nylon PA 66.
- Application : The refined polyamide ferrules are designed to protect cables from contacting the sharp edged conduit. AVC's high-grade ferrules have the best performance in chemical, oil, rust and weather resistance, which are suitable for the constructions of machineries and installations of equipments.



270-8020

Metal Ferrules For Convolved Conduits

RoHS Compliant



Cat. No.	For Sizes	Dimensions				Std. Pkg. pcs
		A mm	B1 mm	B2 mm	C mm	
S - FM02	1/4 "	7.3	13	14.9	11	10
S - FM02.5	5/16 "	9.3	16.5	16.7	14.3	10
S - FM03	3/8 "	11	19.5	20.9	16.9	10
S - FM04	1/2 "	14.5	23	24.8	18.2	10
S - FM06	3/4 "	19.5	28.1	30.5	18	10
S - FM08	1 "	24.5	35.5	37	22.5	10
S - FM10	1 1/4 "	33	45	48.6	24.5	5
S - FM12	1 1/2 "	38	50.5	53	26.5	5
S - FM16	2 "	49	62	65	32	5
S - FM20	2 1/2 "	59.5	75	80.6	38.5	1
S - FM24	3 "	75	91	96	41.5	1
S - FM32	4 "	99	117	121.7	46	1

- Material Data : Galvanized metal.
- Application : In order to protect cables from contacting the sharp edged conduit, the metal ferrules are designed to fit the cut edges of the metal conduits that they do not need to be connected with the fittings.

